



JUST LOW, JUST FIT.


LOW HEIGHT

Low body floor height

Convenient for easy loading goods and unloading Access more areas especially restricted maximum height 2.1 metres Easier for maintenance



Ground to body floor height, h: 880mm *XZU600 (5t) height: 980mm



Mounting brackets available on chassis frame for direct body mounting



Low fuel tank height for lower body mounting

■ Can access more areas especially shopping malls










LOW (SMALL) TURNING RADIUS


Better maneuverability at tight corners





03 LOW NOISE

Quiet but powerful engine
 Flat torque engine - Easy to achieve maximum torque with good fuel efficiency





04 LOW VIBRATION

■ Comfortable and safe driving with front independent suspension



Safe

Better tyre contact at uneven road surface condition

Double wishbone structure

05 OTHER FEATURES

■ Functions that provide better control to driver at emergency situations



ANTI LOCK BRAKING SYSTEM

Prevents wheel lock up during emergency braking



VEHICLE STABILITY CONTROL

Ensures vehicle direction = steering direction at all times, especially during sudden swerve



TRACTION CONTROL

Improves maneuverability and vehicle stability especially during start acceleration on slippery condition

SPECIFICATION

		MODEL	200 Series
ITEM		MODEL CODE	GDY231R-HBMLP3
I I - IVI	MODEL	WODEL CODE	TOYOTA 1GD-FTV
ENGINE	TYPE		Diesel, turbocharged and intercooled, in-line 4-cylinder, double overhead camshaft, water-cooled
	DISPLACEMENT	СС	2,754
	MAX OUTPUT	PS/rpm	144 / 3,400
	MAX. TORQUE	Nm/rpm	300 / 1,200-3,200
	BORE & STROKE	mm	92 x 103.6
	FUEL INJECTION SYSTEM		Electronic Control Commonrail
	AIR INTAKE SYSTEM		Under cab mounted air intake with air filter
	MAX.ENGINE SPEED	rpm	4,400
OLLITOLI	TYPE		Dry single plate with damper springs, hydraulic control
CLUTCH	DIAMETER	mm	275
AXLE	FRONT	Туре	Independent
		kg	1,800
	REAR	Туре	Full-floating, single reduction, single speed by hypoid gearings
		kg	2,300
BRAKE	SERVICE BRAKE TYPE		Hydraulic System with Ventilated Disc for Front Wheels and Dual Two (2) Leading Shoes for Rear Wheels
	SERVICE BRAKE CONTROL		Vacuum Servo Hydraulic, Dual Circuits with ABS and VSC
	PARKING BRAKE TYPE	T) (DE	Mechanical, internal expanding acting on transmission output shaft
SUSPENSION	FRONT	TYPE	Double wishbone, independent torsion bar springs with double acting shock absorbers and stabiliser bar
	REAR	TYPE	Semi-elliptic main and auxiliary leaf springs and rubber rebound bumpers with double acting shock absorbers
FRAME	WIDTH	LL-MAG.T.	800
	DIMENSION TILTING	HxWxT	160 x 50 x 4.5
CABIN EQUIPMENT	STEERING		Mechanical Type
	POWER WINDOW	TYPE	Telescopic and tilt steering column, rack and pinion power steering
	CENTRAL LOCKING	ITPE	Equipped Equipped
	SEAT BELT		Equipped
WHEELS & TIRES	WHEEL TYPE		6 Stud disc wheel
	RIM SIZE		15 x 5J
	TIRE SIZE TYPE		195/75R15
ELECTRICAL	BATTERIES		12V, negative ground 12V, 80 Ah
	ALTERNATOR CAPACITY	V - A	12V, 60 AH
FUEL TANK CAPACITY	ALIENWATORI GALAGITT	Liter	80
PERFORMANCE		Entor	
G.V.W Rating		kg	3,600
	MAX SPEED	km/h	100 (speed limiter)
PERFORMANCE	GRADEABILITY	Tan %	46.1
TRANSMISSION	MODEL		R451 / 5F-1R
	TYPE		Manual
	GEAR RATIO 1st		4.313
	2nd		2.330
	3rd		1.436
	4th		1.000
	5th		0.838
	Reverse		4,220
REAR AXLE	RATIO		4.100
DIMENSION & MASS			
CHASSIS MASS (with std. tools	FRONT	kg	1,175
set & spare tire)	REAR	kg	520
	TOTAL	kg	1,695
DIMENSION	WHEELBASE OVERALL LENGTH	mm	2,545 4 565
	OVERALL LENGTH OVERALL HEIGHT	mm	4,565 1,990
	OVERALL HEIGHT	mm mm	1,695
	CAB TO REAR AXLE		
		mm	1,990
	FRONT OVERHANG	mm	960
	REAR OVERHANG	mm	1,015
	Fr FRAME HEIGHT	mm	635
	Rr FRAME HEIGHT	mm	710
	EDONT TOTAL		1 110
	FRONT TREAD REAR TREAD	mm mm	1,440 1,400



HINO MOTORS SALES (MALAYSIA) SDN BHD (187863-U)

Selangor: Lot PT 24, Jalan 223, Section 51A, 46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia. Tel: (603) 7957 5199 (12 lines) Fax: (603) 7954 3276 Sarawak: Lot 1076, Block 218, 4th Mile, Penrissen Road, 93250 Kuching, Sarawak, Malaysia. Tel: (082) 451 611 (5 lines) Fax: (082) 451 993 Sabah: Miles 4 1/2 Jalan Tuaran, Lot No. 353, Taman Cempaka, Likas, 88450 Kota Kinabalu, Sabah, Malaysia. Tel: (088) 393 663 Fax: (088) 424 223

www.hino.com.my









HINO Authorized Dealer: