


SPECIFICATION

		MODEL	XZU720LC
ITEM	MODEL CODE		XZU720R - QKMQL3
ENGINE	MODEL		N04C-VB
	TYPE		Diesel, 4-cy.,vertical, 4-cyl. in-line, overhead valve, water cooled, direct injection
	DISPLACEMENT		cc
	MAX OUTPUT (JIS GROSS)		kW(PS)/rpm
	MAX. TORQUE (JIS GROSS)		Nm(kgfm)/rpm
	BORE & STROKE		mm
	FUEL INJECTION SYSTEM		Electronic control Commonrail type
	AIR INTAKE SYSTEM		Turbo-intercooled, stack type
CLUTCH	MAX.ENGINE SPEED		rpm
	TYPE		Dry single plate, diaphragm type with damper spring
TRANSMISSION	DIAMETER		mm
	MODEL/NO. OF SPEED		M550 / Manual 5-Speed
	TYPE		Five (5) forward and one (1) reverse, overdrive, synchromesh 1 st - 5 th
AXLE	RATIO (1st - Top)		4.981 / 0.738
	FRONT	TYPE	Reversed Elliot, "I" section beam
		CAPACITY	kg
	REAR	TYPE	Full floating, single reduction, single speed by hypoid gearing
BRAKE			5,100
	SERVICE BRAKE TYPE		Hydraulic system with two leading shoes for front wheels and dual two leading shoes for rear wheels with auto brake shoe adjuster
	SERVICE BRAKE CONTROL		Vacuum servo hydraulic, dual circuits with Antilock Braking System (ABS) and power assist
	PARKING BRAKE TYPE		Mechanical, internal expanding, acting on transmission output shaft
SUSPENSION	EXHAUST BRAKE TYPE		Electric-vacuum actuator with valve in exhaust pipe
	FRONT	TYPE	Semi elliptic leaf spring with dual acting shock absorber and stabilizer
FRAME	REAR		Semi elliptic main and auxiliary leaf spring with dual acting shock absorber
	FRAME WIDTH		mm
CABIN	HEIGHT x WIDTH x THICKNESS		mm
	TILTING		750
	STEERING		192.8 x 65 x 5.9
	HINO ARMTECH		Rigid Type
	POWER WINDOW		Telescopic & tilt steering column with locking device, recirculating ball with hydraulic booster, integral type
	CENTRAL LOCKING		Equipped
WHEELS & TIRES	SEAT BELT		Equipped
	WHEEL TYPE		Equipped
	RIM SIZE		Equipped
ELECTRICAL	TIRE SIZE		Equipped
	TYPE		24V, Negative Earth
	BATTERIES		12V x 2 , Series connection
FUEL TANK CAPACITY	ALTERNATOR CAPACITY		24V - 60 Amps
			L
PERFORMANCE			
G.V.W Rating			kg
PERFORMANCE	MAX SPEED		km/h
	GRADEABILITY		(tan Ø) %
TRANSMISSION RATIO	MODEL		M550
	1st		4.981
	2nd		2.911
	3rd		1.556
	4th		1.000
	5th		0.738
	REVERSE		4.625
REAR AXLE	MODEL		SH12
	RATIO		5.125
DIMENSION & MASS			
CHASSIS MASS (with std tools set & spare tire)	FRONT AXLE		kg
	REAR AXLE		kg
	TOTAL		kg
DIMENSION	WHEELBASE		WB
	OVERALL LENGTH		OL
	OVERALL WIDTH		OW
	OVERALL HEIGHT		OH
	CAB TO AXLE CENTER		CA
	FRONT OVERHANG		FOH
	REAR OVERHANG		ROH
	FRONT TREAD		FT
	REAR TREAD		RT
	TURNING RADIUS (on tire)		mm
	SEATING CAPACITY		

HINO MOTORS SALES (MALAYSIA) SDN. BHD. is engaged in an ongoing research and development program, and reserves the right to change specification without prior notice in order to pass on to the customer any resulting advances or technical refinements. All specifications of the product are within normal manufacturing allowances and tolerances.



Ver. 04/10.2019



HINO 300 SERIES

Compliance with United Nations Regulation (UNR) by JPJ



XZU720 CREW 156ps

Designed GVW 7,500 kg
(6 Wheeler)

WARRANTY
5 YEARS
or
200,000KM
Terms and conditions apply

FREE*
SERVICE PROGRAM
3 TIMES
(1~3rd Service)

FREE*
PARTS PROGRAM
7 TIMES
(4th~10th Service)

PROTECTED BY
HINO
ArmTech

BREAKDOWN
24 HOURS
SERVICE
Applicable to West Malaysia
Toll Free: 1800-88-3666


Terms and Conditions apply*

HINO MOTORS SALES (MALAYSIA) SDN BHD (187863-U)

Selangor: Lot PT 24, Jalan 223, Section 51A, 46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia. Tel: (603) 7957 5199 (12 lines) Fax: (603) 7954 3276
Sarawak: No. 230, Lot 3477, Block 226, KKND (P/L 2543), Jalan Kung Phin 93250 Kuching, Sarawak, Malaysia. Tel: (082) 451 611 (5 lines) Fax: (082) 451 993
Sabah: Miles 4 1/2 Jalan Tuaran, Lot No. 353, Taman Cempaka, Likas, 88450 Kota Kinabalu, Sabah, Malaysia. Tel: (088) 393 663 Fax: (088) 424 223



www.hino.com.my

PERFORMANCE




EURO3
XZU720 CREW

Model:
N04C-VB
Type:
**4,009cc 4-cylinder in-line
Electronic Control
Commonrail**
Output (kW/rpm):
114 (156PS)/2,800rpm
Torque (Nm/rpm):
429Nm (43.8kgfm)/1,400rpm



Frame


The frame is both very strong and lightweight



Suspension

The leaf spring suspension offers high durability and flexibility for stability on rough roads.

COMFORTABILITY



Seat Slide

The seat rails are set on an incline to accommodate your seating position.



Folding Type Shift Lever

The shift lever and side lever fold down, making it easy to move around the driver compartment.



Ergonomics and Accessibility (Crew Cab: Rear Seat)

Plenty of space for 4 adults (*2 adults shown).
Generous storage space when the seat is stowed.
*Seating capacity: 7 seater (Subject to JPJ Approval)



LED Meter Panel

The meter cluster features highly visible readouts of necessary vehicle information.



Overhead Console


Greater convenience for documents storage with open section which allows easy access.



Work Space

Intuitively designed, spacious and comfortable, the cab space allows drivers to perform at their best.

SAFETY



Antilock Braking System (ABS)

ABS helps the driver maintain control of the vehicle when braking on a slippery surface by selectively controlling the braking force of individual wheel in order to prevent the wheels from locking.



EGIS Cab (Emergency Guard Impact Safety)

The EGIS Cab Design is one of HINO'S passive safety features, enhancing the rigidity of the cab.



Drum Brake

Equipped with auto brake shoe adjuster to ensure safe & effective braking. It features easy maintenance without compromising on performance.



Tubeless Tyres

Provides good tyre puncture resistance for better safety. Better fuel efficiency due to lighter tyre and lower rolling resistance.



Stabilizer

The stabilizer have been lengthened and feature a link bracket, maintaining high effectiveness and stability.



Door Impact Beams

The side impact beams built into the doors of 300 Series increase the level of protection for driver and passenger in the event of a collision from the side.




Side Mirror

The door-mounted outer mirrors enhance driver's vision. It features partitioned mirror surfaces encased in an aerodynamic and low-profile shell.



Wide View Pillars

The front pillars are designed to be as narrow as possible to ensure a nearly uninterrupted view, allowing the driver to easily see pedestrians and cyclist, without any compromise in structural integrity.



Energy-Absorbing Steering Wheel and Column


The energy-absorbing steering wheel and column reduce collision force.



Headlamp Leveling Switch

The Headlamp Leveling Switch can be used to adjust the headlamp illumination distance.

APPLICATION



Model	XZU720 CREW	
Standard	14'10"	
Optional	13'9"	15'6"


○ Drive Axle

Body Type


A truck for every application of bodies suit your type of business.



General Cargo




Box




Curtain Sider



Refrigerated




Tipper




Crane Cargo



Roll On Roll off



Tanker



Garbage Compactor

Note : Some images may be used for illustration purposes only.